

SFC 407g Gold- The legendary Tata 407 goes Green**Rebirth of the legend to create Gold like Business Value 'Non-Stop Profit Machine'**

Tapping into the benefits of CNG, the all-new SFC 407g CNG has been designed to live up to its reputation as the 'non-stop profit machine', continuing to offer best-in-class performance and reliability, and adding even more value to the proposition with lower TCO. The vehicle is available with a 10-foot load deck, offering a high load-carrying capacity. The all-new SFC 407g CNG will further strengthen Tata Motors' extensive CNG portfolio, ranging from 5-tonne to 16-tonne gross vehicle weight (GVW), in the I&LCV segment.

SFC 407g CNG is powered by a 3.8-litre CNG engine leveraging the fuel-efficient SGI engine technology and delivers maximum power of 85PS while also generating best-in-class torque of 285Nm at low rpm. The 4,995kg-GVW vehicle is equipped with a fuel tank capacity of 180 litres to ensure faster turnaround time and higher productivity. The iconic SFC (semi-forward control) cabin of the 407 is built with high-grade steel, making it safe and confidence-inspiring for drivers and owners alike. The 407 rides on front parabolic suspension, offers significantly reduced clutch and gear shift effort and low NVH levels, to offer the best comfort on all types of terrains. For the convenience and in cabin entertainment of the driver, the vehicle is equipped with a USB mobile charging port and Blaupunkt music system. The 407g range now comes loaded with the Fleet Edge – Tata Motors' next-gen connected vehicle platform for optimal fleet management, to further increase the uptime and reduce the total cost of ownership, with a free subscription of 2 years.

SFC407g is built around the 'Power of 6' philosophy of Tata Motors BS6 I&LCV range with focus on: Power of Business Profit, Power of Vehicle Performance, Power of Driving Comfort, Power of Convenience & Connectivity, Power of Value and Power of Safety and Security.

Feature Highlights:

- The iconic SFC (semi-forward control) refresh cabin of the 407 is built with high-grade steel, making it safe and confidence-inspiring for drivers and owners
- 2T+ Payload with 4.9T GVW,
- Power Steering
- 10Ft Clear Internal Deck length Load body
- 7.50R16 -14PR Tyres, Radial tyre for Better Loading capacity
- Advanced Cabin features such as music system, mobile charger, heat resistant seats, height, inclination and slide adjustable seats, Melba Fabric for Seats for better comfort both in summer and winter
- New Instrument Cluster
- H2LS Brakes with Brake Boosters
- Lowest rear overhang for better stability
- Banjo Type Rear Axle More Load carrying capacity, lesser prone to leakage
- Long member thickness is increased to 5mm
- Gradeability Improvement (~31%+)
- Advanced Telematics Connectivity with App for Owners and Fleet managers

Applications Suitable for:

E-Commerce, Logistics Services, Couriers, Pharma, Reefers (fresh delivery of perishable goods), White goods, FMCG, LPG Cylinder carriers, Water Tanker, Poultry, Fruits, Vegetables and Municipal applications.

Technical specifications:**Model Specifications****SFC 407g GOLD**

for immediate use

PRODUCT NOTE

Engine:	3.8 SGI BS6 4 Cylinder
Max. Power :	85 PS (62KW) @2500 r/min
Max. Torque :	285 Nm @ 1200 -1600 r/min
Clutch :	280 mm Dia
Transmission :	G400, 5 Speed, Manual Synchromesh Gearbox (5F, 1R)- PTOP
No. of gears :	5Forward & 1 Reverse
Front suspension :	Parabolic Leaf springs Hydraulic Double acting telescopic type Shock Absorbers with Antiroll bar.
Rear suspension :	Semi elliptical leaf spring, 2 no Hydraulic Double acting Shock Absorbers
Steering :	Power Steering
Brakes :	New H2LS Brakes: Vaccum assisted; Hydraulic two leading slide shoe; Auto Slack Adjuster
Tyres :	7.50R16 -16PR
Fuel tank capacity :	180 L (2 X 90 L)
Gross Vehicle Weight (GVW) :	4995kg
Seating capacity :	DRIVER +2
Max. speed :	80 kmph
Grade ability :	31%
Turning radius :	6.5 m
Dimensions - outer in mm (LxWxH) :	5412 x 2100 X 2960 (HD)
Wheelbase :	3305mm
Load body dimensions inner in mm (LxWxH) :	10 Ft X 6.5 Ft (3070 x 1965 x 1835)mm