

LPT 510 10Ft - Game changer of your Business

LPT 510 is a unique 10Ft load body on LPT cabin version with lowest wheelbase for last-mile narrow lane delivery application with the highest GVW (5490kg) in this segment.

It comes with:

- ✓ 3 decades of reliability and trust of LPT brand, Highest Resale Value
- ✓ With minimum turning radius and lower wheelbase it cater to various narrow lane applications
- ✓ Heavy duty aggregates for more Durability
- ✓ Highest Driver Safety due to and all Steel Cabin
- ✓ Lowest Maintenance cost

Feature Highlights:

- 2.4T Payload with Highest GVW in this segment - 5.49T GVW
- Trusted and reliable 4SPCR engine with Better power and torque with flat torque which assures best in class mileage.
- 10.6 ft+ Internal Load body
- Power Steering with reduced effort, New Steering Wheel and combination Switch
- 37% Gradeability – Highest ever in this Class
- Smaller Turning radius 5.1m for ease to travel in narrow lane applications
- Radial tube tyre 7.5R16 -16 PR
- Strongest chassis in its class with 5 mm thickness
- IL SPLIT TYPE H2LS Braking system for effective braking
- Bigger Clutch size of 280 mm dia for longer life and easy gear shifting
- All Steel LPT Cabins for Better safety
- Banjo Type Rear Axle More Load carrying capacity, lesser prone to leakage
- USB mobile charging port and Blaupunkt music system.
- Advanced Telematics Connectivity with App for Owners and Fleet managers
- New Instrument Cluster with Tell-tale Symbols and Gear shift advisor

Applications Suitable for:

E-Commerce, Logistics Services, Couriers, Pharma, Reefers (fresh delivery of perishable goods), White goods, FMCG, LPG Cylinder carriers, Water Tanker, Poultry, Fruits, Vegetables and Municipal applications.

Technical specifications:

Model Specifications	LPT 510 10 FT, 2775 WB, 5.49T
Engine:	4SPCR BS6
Max. Power :	100PS @2800 r/min
Max. Torque :	300 Nm @ 1200 -2200 r/min
Clutch :	280 mm Dia
Transmission :	G400, 5 Speed, Manual Synchromesh Gearbox (5F, 1R), PTOP
No. of gears :	5Forward & 1 Reverse

for immediate use

PRODUCT NOTE

Front suspension :	Semi elliptical leaf spring and Hydraulic double acting telescopic type Shock Absorber
Rear suspension :	Semi elliptical leaf spring
Steering :	Power Steering
Brakes :	IL SPLIT TYPE H2LS
Tyres :	7.5R16 -16 PR
Fuel tank capacity :	60 L
Gross Vehicle Weight (GVW) :	5490kg
Seating capacity :	DRIVER +1
Grade ability :	37%
Turning radius :	5.1m
Dimensions - outer in mm (LxWxH) :	5215 X 2255 X 2326mm (HD)
Wheelbase :	2775mm
Load body dimensions inner in mm (LxWxH) :	10.6 ft (3245 x 2117 x 1814)mm